

Ground Joint Couplings for Use With Crimped Ferrules

NEW
ITEMS



Hose Stem with Interlocking Collar

Part Number	Size (in.)	Air Crimp (psi)	Weight Each (lbs.)	Standard Carton
GJS-CR050	1/2	600	0.23	200
GJS-CR075	3/4	600	0.54	100
GJS-CR100	1	600	0.59	100
GJS-CR125	1 1/4	600	1.11	32
GJS-CR150	1 1/2	600	1.21	35
GJS-CR200	2	600	1.87	25
GJS-CR250	2 1/2	400	3.57	10
GJS-CR300	3	400	4.68	8
GJS-CR400	4	400	8.81	4

Note: Ground Joint fittings with interlocking collars are not for use with steam hose.

NEW
ITEMS



Threaded Male Hose Shank with Interlocking Collar (NPT Threads)

Part Number	Size (in.)	Air Crimp (psi)	Weight Each (lbs.)	Standard Carton
GJM-CR050	1/2	600	0.22	250
GJM-CR075	3/4	600	0.43	250
GJM-CR100	1	600	0.66	100
GJM-CR125	1 1/4	600	1.28	32
GJM-CR150	1 1/2	600	1.36	25
GJM-CR200	2	600	2.32	20
GJM-CR250	2 1/2	400	4.06	8
GJM-CR300	3	400	5.63	6
GJM-CR400	4	400	10.79	3

Note: Ground Joint fittings with interlocking collars are not for use with steam hose.

Interlocking Bolt Clamps

NEW
ITEMS

4 Bolt Hose Clamp (Recommended for use with Ground Joint Couplings)



Part Number	Size (in.)	Weight Each (lbs.)	Torque (ft. lbs.)	Standard Carton
BC4-100	1 17/32 - 1 23/32	1.50	21	24
BC4-100A	1 13/32 - 1 9/16	1.54	21	24
BC4-100B	1 11/16 - 1 27/32	1.68	21	24
BC4-100C	1 7/8 - 2 1/16	1.90	21	20
BC4-125	2 1/16 - 2 1/4	2.36	40	20
BC4-150S	1 13/16 - 2	2.49	40	20
BC4-150	2 - 2 17/32	2.40	40	20
BC4-150A	2 3/32 - 2 9/32	2.56	40	20
BC4-150B	2 1/4 - 2 7/16	2.78	40	20
BC4-150C	2 15/32 - 2 23/32	2.67	40	20
BC4-200	2 11/32 - 2 17/32	3.04	60	20
BC4-200A	2 1/2 - 2 25/32	2.84	60	20
BC4-200B	2 3/4 - 3 1/16	3.99	60	16
BC4-200C	3 3/32 - 3 7/16	3.97	60	14
BC4-250	3 1/2 - 3 15/16	6.86	150	5
BC4-300	3 1/2 - 3 15/16	7.45	150	5
BC4-300A	3 13/16 - 4 1/16	7.89	150	5
BC4-300B	4 1/16 - 4 7/16	10.19	200	4
BC4-300C	4 - 4 3/16	10.30	200	4

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.