



T760LE Series 75 PSI Dry Bulk Food Discharge Hose

General Applications:

Discharge or delivery of dry bulk food products.

Construction:

Tube: 3/16" white NR – abrasion resistant. Meets FDA requirements.

Reinforcement: Spiraled high tensile textile cords with static wire.

Cover: Blue SBR/EPDM – abrasion and ozone resistant.

Working Pressure:

Constant Pressure – 5 Bar (75 PSI)

Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T760 5 BAR (75 PSI) – BULK FOOD & MATERIAL DELIVERY (in white letters)

Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
T760LE400	4	102	4.65	118	75	100	2.12

★ Please note: Proper grounding of static wire will prolong tube life.

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 36.

COUPLING SUGGESTIONS

Quick-Acting coupling attached with bands.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.