



T763AA Series 75 PSI Heavy Weight Dry Powder Delivery Hose

General Applications:

Discharge of dry powders under low pressure. Pneumatic transfer of dry materials and abrasive slurries.

Construction:

Tube: 1/4" black static conducting NR – compounded to resist cutting by abrasive materials.

Reinforcement: Spiraled high tensile textile cords.

Cover: Black conductive SBR/NR blend – abrasion and ozone resistant.

Working Pressure:

Constant Pressure – 5 Bar (75 PSI)

Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T763 5 BAR (75 PSI) BULK MATERIAL DELIVERY (in green letters)

Nominal Specifications

| Series Number | ID (in) | ID (mm) | OD (in) | OD (mm) | Max Rec. WP (psi) | Standard Length (ft) | Weight (lbs/ft) |
|---------------|---------|---------|---------|---------|-------------------|----------------------|-----------------|
| T763AA400 | 4 | 102 | 4.72 | 120 | 75 | 100 | 2.14 |
| T763AA450 | 4 1/2 | 115 | 5.24 | 133 | 75 | 100 | 2.30 |
| T763AA500 | 5 | 127 | 5.71 | 145 | 75 | 100 | 2.60 |

★ Excessive bending during operation may cause premature wear.

COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.