



Ductile Iron Quick-Acting Couplings “Maximum Flow Design”



Ductile Iron Part C Female Coupler x Hose Shank

| Part Number | Size (in.) | Weight Each (lbs.) | Standard Carton |
|-------------|------------|--------------------|-----------------|
| DI-C400 | 4 | 7.29 | 15 |



Ductile Iron Part E Male Adapter x Hose Shank

| Part Number | Size (in.) | Weight Each (lbs.) | Standard Carton |
|-------------|------------|--------------------|-----------------|
| DI-E400 | 4 | 5.84 | 20 |

ALSH Aluminum Quick-Acting Couplings Supplied with Stainless Steel Handles, Slot Pins, Safety Clips & Pull Rings



Aluminum Part B Female Coupler x Male NPT

| Part Number | Size (in.) | Weight Each (lbs.) | Standard Carton |
|-------------|------------|--------------------|-----------------|
| ALSH-B100 | 1 | 0.36 | 25 |
| ALSH-B125 | 1 1/4 | 0.62 | 20 |
| ALSH-B150 | 1 1/2 | 0.70 | 12 |
| ALSH-B200 | 2 | 0.86 | 10 |
| ALSH-B250 | 2 1/2 | 1.02 | 12 |
| ALSH-B300 | 3 | 1.56 | 8 |
| ALSH-B400 | 4 | 2.42 | 12 |



Aluminum Part D Female Coupler x Female NPT

| Part Number | Size (in.) | Weight Each (lbs.) | Standard Carton |
|-------------|------------|--------------------|-----------------|
| ALSH-D100 | 1 | 0.42 | 25 |
| ALSH-D125 | 1 1/4 | 0.68 | 20 |
| ALSH-D150 | 1 1/2 | 0.80 | 12 |
| ALSH-D200 | 2 | 0.92 | 10 |
| ALSH-D250 | 2 1/2 | 1.18 | 12 |
| ALSH-D300 | 3 | 1.80 | 10 |
| ALSH-D400 | 4 | 2.82 | 10 |



Aluminum Part C Female Coupler x Hose Shank

| Part Number | Size (in.) | Weight Each (lbs.) | Standard Carton |
|-------------|------------|--------------------|-----------------|
| ALSH-C100 | 1 | 0.42 | 25 |
| ALSH-C125 | 1 1/4 | 0.68 | 20 |
| ALSH-C150 | 1 1/2 | 0.74 | 10 |
| ALSH-C200 | 2 | 0.98 | 12 |
| ALSH-C250 | 2 1/2 | 1.28 | 12 |
| ALSH-C300 | 3 | 2.20 | 5 |
| ALSH-C400 | 4 | 3.16 | 6 |



Aluminum Part DC Dust Cap

| Part Number | Size (in.) | Weight Each (lbs.) | Standard Carton |
|-------------|------------|--------------------|-----------------|
| ALSH-DC100 | 1 | 0.34 | 25 |
| ALSH-DC125 | 1 1/4 | 0.58 | 20 |
| ALSH-DC150 | 1 1/2 | 0.64 | 25 |
| ALSH-DC200 | 2 | 0.80 | 20 |
| ALSH-DC250 | 2 1/2 | 0.94 | 12 |
| ALSH-DC300 | 3 | 1.44 | 8 |
| ALSH-DC400 | 4 | 2.34 | 6 |

See applications and specifications on pages 25 & 27.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.