



## Quick-Acting Coupling Specifications

### Applications

Agriculture • Chemicals • Petroleum • Construction • Material Handling • Irrigation • Fracking

## Polypropylene

### Features & Benefits

- All sizes except 1/2" comply with Mil-Spec A-A-59326 for interchangeability
- 1/2" x 1/2" are not specified under Mil Specs
- Polypropylene material is glass-filled for added strength and durability
- Locking feature using safety clips to prevent disconnection during use on all sizes except 1/2"
- All 4" size female couplers are supplied with three locking handles to provide added stability

### Material Specifications

- Type 304 stainless steel handles
- Type 304 stainless steel handle pins
- Type 304 stainless steel pull rings
- Type 304 stainless steel safety clips
- EPDM gaskets

### PSI Rating @ 70°F (+21°C)

|           |         |
|-----------|---------|
| 1/2" - 2" | 100 PSI |
| 3" - 4"   | 50 PSI  |

## Glass Reinforced Nylon

### Features & Benefits

- All sizes comply with Mil-Spec A-A-59326 for interchangeability
- Nylon material is fiberglass reinforced for high tensile strength and durability
- Locking feature using safety clips to prevent disconnection during use on all sizes
- All 4" size female couplers are supplied with three locking handles to provide added stability

### Material Specifications

- Type 304 stainless steel handles
- Type 304 stainless steel handle pins
- Type 304 stainless steel pull rings
- Type 304 stainless steel safety clips
- EPDM gaskets

### PSI Rating @ 70°F (+21°C)

|           |         |
|-----------|---------|
| 1/2" - 2" | 100 PSI |
| 3" - 4"   | 50 PSI  |

## Ductile Iron

### Features & Benefits

- All sizes comply with Mil-Spec A-A-59326 for interchangeability
- Coupling ID is specially designed for maximum flow of product
- Locking feature using safety clips to prevent disconnection during use on all sizes

### Material Specifications

- Type 304 stainless steel handles
- Type 304 stainless steel handle pins
- Type 304 stainless steel pull rings
- Zinc-plated carbon steel safety clips
- BUNA gaskets

### PSI Rating @ 70°F (+21°C)

|    |         |
|----|---------|
| 4" | 150 PSI |
|----|---------|

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.